



400 Watt MINI-SOFT

Model # L3000

STURDY STEEL CONSTRUCTION

- Colour frame brackets
- Solid and perforated steel
- Designed coated diffuser
- Deep trough reflector
- Comes with on and off switch
- Provides smooth, indirect, soft light
- May be mounted on motion picture television cameras
- Well ventilated
- C.S.A. NRTL/C approved

Applications:

- Television Studios
- Video production
- Motion Pictures
- Still photography

Specifications:



The unit is a 400w Soft light fixture that is equipped with an eight foot cable, on and off single pole switch and U-ground connector. It is designed so that all light passes indirectly from the diffuser to create a virtually shadow free, soft, smooth field. The housing is constructed of 22 gauge and 20 gauge steel, formed and properly ventilated for cool operation. Relamping is easily accomplished by loosening a single thumb screw allowing the hinged diffuser to swing away from the main housing.

- Supplied with 750 spigot block
- Standard black finish
- C-clamp available
- Stacking grids available
- Lamps: FAD-400

Rating: 120/240 Volts A.C. or D.C.
3.3 Amps Max. 400 Watts

Cable: 8 feet of #18/3 SJT cable c/w U-ground plug

Socket: Two compressible contacts

Weight: 2 Kg., 5 Lbs.

SECTION

1.2