



## 1000 Watt MINI-SOFT

### Model # L3200

#### STURDY STEEL CONSTRUCTION

- Hinged colour frame
- Solid and perforated steel
- Designed coated diffuser
- Deep trough reflector
- Comes with on and off switch
- Provides smooth, indirect, soft light
- Well ventilated
- C.S.A NRTL/C approved

#### Applications:

- Television Studios
- Motion Pictures
- Commercials
- Video production
- Still photography

#### Specifications:

The unit is a 1000w Soft light fixture that is equipped with an eleven foot cable and an on-off single pole switch. It is designed so that all light passes indirectly from the diffuser to create a virtually shadow free, soft, smooth field. The housing is constructed of 22 gauge and 20 gauge steel, formed and properly ventilated for cool operation. Relamping is easily accomplished by loosening a single thumb screw allowing the hinged diffuser to swing away from the main housing.

- Supplied with 750 spigot block
- Standard black finish
- C-clamp optional
- Stacking grids optional
- Lamps: FCM, FND, FHM  
Q1000

Rating: 120/240 Volts A.C. or D.C.

8.3 Amps Max. 1000 Watts

Cable: 3 feet of #14 ga, three SEW leads sheathed to switch  
box, SJOW from switch box.

Socket: Two compressible contacts

Weight: 3 Kg., 6.5 Lbs.



SECTION

1.3