



2000 Watt MINI-SOFT

Model # L3300

STURDY STEEL CONSTRUCTION

- Hinged colour frame
- Solid and perforated steel
- Designed coated diffuser
- Deep trough reflector
- Dual switching for intensity control
- Provides smooth, indirect, soft light
- Well ventilated
- C.S.A. NRTL/C approved

Applications:

- Television Studios
- Motion Pictures
- Commercials
- Video production
- Still photography

Specifications:

The unit is a 2 -1000w Soft light fixture that is equipped with an eleven foot cable, on-off switches for intensity control. It is designed so that all light passes indirectly from the diffuser to create a virtually shadow free, soft, smooth field. The housing is constructed of 22 gauge and 20 gauge steel, formed and properly ventilated for cool operation. The replacement of the double end tungsten halogen lamps is easily accomplished by loosening a single thumb screw, allowing the hinged diffuser to swing away from the main housing.

- Supplied with 750 spigot block
- Standard black finish
- C-clamp available
- Stacking grids available
- Lamps: FCM, FND, FHM
Q1000

Rating: 120/240 Volts A.C. or D.C.

16.6 Amps Max. 2000 Wats

Cable: 3 feet, 4 SEW #14 ga sheathed leads to switch box.

12/3 SJOW from switch box to tails

Socket: Two compressible contacts per lamp

Weight: 5.5 Kg., 12 Lbs.



NRTL /C

SECTION

1.4