



## 4000 Watt MINI-SOFT

### Model # L3400

#### STURDY STEEL CONSTRUCTION

- Hinged colour frame
- Solid and perforated steel
- Designed coated diffuser
- Deep trough, specular aluminum reflector
- Individual lamp control for intensity
- Provides smooth, indirect, soft light
- Well ventilated
- C.S.A NRTL/C approved

#### Applications:

- Television Studios
- Still Photography
- Motion Pictures
- Commercials



#### Specifications:

The unit is a 4-1000w Soft light fixture that is equipped with 4 switches to control light intensity. It is designed so that all light passes indirectly from the diffuser to create a virtually shadow free, soft, smooth field. The housing is constructed of 22 gauge and 20 gauge steel, formed and properly ventilated for cool operation. The replacement of the double end tungsten halogen lamps is easily accomplished by loosening a single thumb screw, allowing the hinged diffuser to swing away from the main housing.

- Standard black finish
- Stacking grids available
- C-clamp available
- Lamps: FCM, FND, FHM  
Q1000

Rating: 120/240 Volts A.C. or D.C.  
33.2 Amps Max. 4000 Watts

Cable: T.B.A.

Socket: Two compressible contacts per lamp

Weight: 22 Kg., 48 Lbs.

SECTION

1.5